



BLUEOCEAN LIGHTING

LED SLIM PANEL DOWNLIGHT

Blue Ocean's **BOL-SRP LED Slim Panel Downlight** series designed to replace downlight luminaires based on CFL and incandescent lamp technology. It is an excellent solution to down lighting for shallow ceilings in homes, offices and hotel hallways etc. Not only the product offers color consistency, comfortable and stable performance high quality lights but also instant energy savings and a much longer life time.

FEATURES

- Slim design with only 0.5" thickness for shallow ceilings
- Aluminum die-cast housing with baking varnish finishing
- Diffuse light quality
- Choice of 4 inch 10W 650lm and 6 inch panel 15W 1200lm
- Choice of colour temperature: 2700K, 3000K, 4000K and 5000K
- High quality SMD2835 LED Chips
- IP43 rated for damp locations
- Operating ambient -20°C to 40°C
- Tri-AC Dimming
- Type IC rated and Airtight
- ETL and ENERGY STAR*
- New construction plate available to ease installation

BENEFITS

- The natural "surface of light"
- Quick and easy Clip-in recessed installation
- No housing required for installation
- 50,000 hour life
- 5 year limited warranty

APPLICATIONS

Blue Ocean Lighting LED Slim Panel Downlights have massive energy savings versus traditional lamps. Coupled with long life, they are superb replacements where standard incandescent, halogen, or fluorescent lamps are in use such as general lighting applications. As well as using at damp locations. Especially the slim design is perfect for applications with shallow ceilings.

COMMERCIAL | INDUSTRIAL | RESIDENTIAL ENVIRONMENTS



IP RATING
43





LED SLIM PANEL DOWNLIGHT

ELECTRICAL AND TECHNICAL DATA

Series No.	Wattage	Replaces	Voltage	Approx. Lumens	Approx. CRI	Available CCT	Beam Angle	IP Rating	Rated Avg. Life(Hrs.)	Warranty (Yrs)
BOL-SRP	10W	65W Inc	120VAC	650lm	>80	2700K 3000K 4000K 5000K	120°	43	50,000	5
BOL-SRP	15W	100W Inc	120VAC	1200lm	>80	2700K 3000K 4000K 5000K	120°	43	50,000	5

SHIPPING DATA

Series No.	Wattage	Case Weight (lb)	Case Cube (cu.ft)	Light Dimensions (DxL) (In.)	Junction Box Dimensions (LxWxH) (In.)	Case Dimensions (LxWxH) (In.)
BOL-SRP	10W	0.8	0.044	4.8x1.0	3.3x3.6x1.1	5.1x5.3x2.9
BOL-SRP	15W	1.4	0.094	7.0x1.0	3.3x3.6x1.1	7.5x7.5x2.9

ORDERING GUIDE

Example: BOL-SRP 4 10W 40 120 D

ORDERING INFORMATION

Series No.	Size	Wattage	CCT	Input Voltage	Dimming
BOL-SRP	4=4inch	10W=10W	27=2700K 30=3000K 40=4000K 50=5000K	120=120VAC	D=Triac Dimming
	6=6inch	15W=15W	27=2700K 30=3000K 40=4000K 50=5000K	120=120VAC	D=Triac Dimming

Rated average life based on engineering testing and probability analysis

For warranty information visit www.blueoceanlighting.com/terms-conditions

*ENERGY STAR is a joint program of the U.S. Environmental Protection Agency and the U.S. Department of Energy helping us all save money and protect the environment through energy efficient products and practices.

More Information at: www.blueoceanlighting.com

