

Project: Notes: Type:

Catalog #:

LED WALL PACK MINI BOLWM

DESCRIPTION

Designed to be an energy efficient, eco-friendly and cost effective replacement for traditional fluorescent, high pressure sodium and metal halide wall packs, Blue Ocean's BOLWM LED Wall Pack Mini series is composed of a shock proof and UV resistant polycarbonate lens and an sealed die-cast aluminum profile with polyester powder-coated finish to resist rust and corrosion. IP65 rated to be free from contaminants, bugs and rain, this LED Wall Pack utilizes built-in high-efficiency UL class 2 driver and superior quality LED chips, providing optimized shelter-free and glare-free illumination, with high energy efficiency, great colour uniformity and minimized lumen depreciation. Built-in photocell is available in 120V and 120-277V versions. Suggested applications: building entrances, stairways, security, residential exteriors, storage and perimeter areas, or anywhere security lighting is needed.



BOLWM-XX

120-277VAC

50W HPS/MH

4000K | 5000K

Dark Bronze

Wall Mount

5.48" X 3.52" X 8.38"

17W

1700lm

>82

>0.9



Model

Voltage Wattage

CRI

PFC

CCT

Finish

Installation

Dimension

Operating Temperature -40~40°C


Replacement


Lumen Output

SPECIFICATION CHART



DRAWING





ORDERING INFORMATION

Series No.	Wattage	Voltage	ССТ	Finish	Sensor	Lens
BOLWM	17W =17W	27V =120-277VAC	40K =4000K	D =Dark Bronze	P2=120-277V Photocell	F=Frosted Lens
	1		50K =5000K	I		




For IES files, please visit: www.blueoceanlighting.com Note: specification subject to change without notice



Project: Notes: Type:

Catalog #:

PHOTOMETRIC SPEC



BLUE OCEAN LIGHTING[™] BOLWM17W

8' Mounting Height

Illuminance at a Distance

	Center Beam LUX	Beam Wid	lth
1.3R	2,605 LUX 🧹	6.0 ft	2.5 ft
2.7ft	604 LUX	12.5 ft	5.2 ft
4.0ft	275 LUX	18.6 ft	7.8 ft
5.3ft	157 LUX	24.6 ft	10.3 ft
5.7R	98.1 LUX	31.1 ft	13.0 ft
3.0ft	68.8 LUX	37.1 ft	15.5 ft

